

Baureihe 5112 1000 – 2000 W

Querschnitt (B x H) 135x115mm

Vakuumimprägniert tw 130

Schutzklasse I

EEL = A2

IP 20



EN 61347 - 2 - 9
EN 60923

Alle Typen mit unterschiedlichen Netzspannungen und in 60 Hz auf Anfrage;



Technische Daten

Pos.	Lampe				Vorschaltgerät				
	Typ	Leistung	Strom	Artikel-Nr.	Bezeichnung	Spannung	ΔT[°K]	Gewicht	
1	HM	1000 W	7,5 A	5112.1120.203	HIS 1000-135.80-34	230-240V / 50Hz	50	13,5 kg	
	HI	1000 W	9,5 A				70		
	HS	1000 W	10,3 A				80		
2	HM / HI	2000 W	8,0 / 8,8 A	5112.1120.201	HI 2000/8-135.70-41	400V / 50Hz	70	13,5 kg	
3	HM / HI	2000 W	8,0 / 8,8 A	5112.1120.215	HI 2000/8-135.70-37	380-400-420V / 50Hz	70	13,5 kg	
neu 4	HI	2000 W	10,3 A	5112.1120.212	HI 2000-135.80.2-41	400V / 50Hz	80	14,0 kg	
5	HI	2000 W	10,3 A	5112.1600.201	HI 2000-135.75-41	400V / 50Hz	75	18,0 kg	
neu 6	HI	2000 W	8,8 A	5112.1120.213	HI 2000-135.80.2-37	380-400V / 50Hz	70	14,0 kg	
	HI	2000 W	10,3 A				80		
7	HI	2000 W	8,8 A	5112.1600.202	HI 2000-135.75-37	380-400V / 50Hz	65	18,0 kg	
	HI	2000 W	10,3 A				75		
neu 8	HI-(HO)	2100 W	11,2 A	5112.1120.214	HI 2000/11-135.85.2-41	400V/50Hz	85	14,0 kg	
neu 9	HI-(HO)	2100 W	11,2 A	5112.1120.216	HI 2000/11-135.85.2-37	380-400-420V/50Hz	85	14,0 kg	
10	HI-(HO)	2100 W	11,2 A	5112.1600.210	HI 2000/11-135.80-37	380-400-420V/50Hz	80	18,0 kg	
neu 11	HI-(HF)	2060 W	12,2 A	5112.1600.211	HI 2000/12-135.80.2-41	400V/50Hz	80	18,0 kg	
neu 12	HI-(HF)	2060 W	12,2 A	5112.1600.212	HI 2000/12-135.80.2-37	380-400-420V/50HZ	80	18,0 kg	

- Schraubklemme 2,5 mm²
- Anzahl der Klemmen je nach Ausführung
- Klemme auf Boden

Ausführung : 5112.1120.xxx

Ausführung : 5112.1600.xxx

