

**Baureihe 5112 1000 – 2000 W**  
**Querschnitt (B x H) 135x115mm**  
**vakuumimprägniert tw 130**

**Schutzklasse I**  
**EEL = A2**  
**IP 20**



**EN 61347 - 2 - 9**  
**EN 60923**

Alle Typen mit unterschiedlichen Netzspannungen und in 50 Hz auf Anfrage;



### Technische Daten

Pos.	Lampe			Vorschaltgerät				
	Typ	Leistung	Strom	Artikel-Nr.	Bezeichnung	Spannung	$\Delta T [K]$	Gewicht
1	HM	1000 W	7,5 A	5112.1120.218	HIS 1000-135.70-6	220V / 60Hz	50	13,5 kg
	HI	1000 W	9,5 A				60	
	HS	1000 W	10,3 A				70	
2	HM	1000 W	7,5 A	5112.1120.225	HIS 1000-135.70-6	220-230-240V / 60Hz	50	13,5 kg
	HI	1000 W	9,5 A				60	
	HS	1000 W	10,3 A				70	
3	HI	2000 W	8,8 A	5112.1120.219	HI 2000/8-135.70-638	380V / 60Hz	70	13,5 kg
4	HI	2000 W	8,8 A	5112.1120.222	HI 2000/8-135.70-637	380-400-420V / 60Hz	70	13,5 kg
5	HI	2000 W	8,8 A	5112.1120.221	HI 2000-135.75-639	380V / 60Hz	65	14,0 kg
	HI	2000 W	10,3 A			380-400V / 60Hz	75	
6	HI	2000 W	8,8 A	5112.1120.226	HI 2000-135.75-637	380-400V / 60Hz	65	14,0 kg
	HI	2000 W	10,3 A			380-400-420V / 60Hz	75	
7	HI	2000 W	10,3 A	5112.1120.220	HI 2000-135.75-638	380V / 60Hz	75	14,0 kg
8	HI-(HO)	2100 W	11,2A	5112.1120.224	HI 2000/11-135.80-637	380-400-420V / 60Hz	80	14,0 kg
9	HI-(HO)	2100 W	11,2 A	5112.1120.223	HI 2000/11-135.80-638	380V / 60Hz	80	14,0 kg
10	H-(HF)	2060 W	12,2 A	5112.1600.224	HI 2000/12-135.75-637	380-400-420V / 60Hz	75	18,0 kg
	H-(HF)	2060 W	12,2 A				5112.1600.225	

- Schraubklemme 2,5 mm<sup>2</sup>
- Anzahl der Klemmen je nach Ausführung
- Klemme auf Boden

Ausführung : 5112.1120.xxx

Ausführung : 5112.1600.xxx

