



Series 5112 **1000 – 2000 W**
Cross section (W x H) **135x115 mm**
vacuum-impregnated

tw 130 **safety class I**
EEI = A2
IP 20



EN 61347 - 2 -9
EN 60923

All types in varios input voltages and 60 Hz version available on request

Technical facts

	Pos.	Typ	lam		Ref.-No.	ballast designation	ballast voltage	ΔT[K]	weight
			power	current					
	1	HM	1000 W	7,5 A	5112.1120.203	HIS 1000-135.80-34	230-240V / 50Hz	50	13,5 kg
		HI	1000 W	9,5 A				70	
		HS	1000 W	10,3 A				80	
	2	HM / HI	2000 W	8,0 / 8,8 A	5112.1120.201	HI 2000/8-135.70-41	400V / 50Hz	70	13,5 kg
	3	HM / HI	2000 W	8,0 / 8,8 A	5112.1120.215	HI 2000/8-135.70-37	380-400-420V / 50Hz	70	13,5 kg
new	4	HI	2000 W	10,3 A	5112.1120.212	HI 2000-135.80.2-41	400V / 50Hz	80	14,0 kg
	5	HI	2000 W	10,3 A	5112.1600.201	HI 2000-135.75-41	400V / 50Hz	75	18,0 kg
new	6	HI	2000 W	8,8 A	5112.1120.213	HI 2000-135.80.2-37	380-400V / 50Hz	70	14,0 kg
		HI	2000 W	10,3 A			380-400-420V / 50Hz	80	
	7	HI	2000 W	8,8 A	5112.1600.202	HI 2000-135.75-37	380-400V / 50Hz	65	18,0 kg
		HI	2000 W	10,3 A			380-400-420V / 50Hz	75	
new	8	HI-(HO)	2100 W	11,2 A	5112.1120.214	HI 2000/11-135.85.2-41	400V/50Hz	85	14,0 kg
new	9	HI-(HO)	2100 W	11,2 A	5112.1120.216	HI 2000/11-135.85.2-37	380-400-420V/50Hz	85	14,0 kg
	10	HI-(HO)	2100 W	11,2 A	5112.1600.210	HI 2000/11-135.80-37	380-400-420V/50Hz	80	18,0 kg
new	11	HI-(HF)	2060 W	12,2 A	5112.1600.211	HI 2000/12-135.80.2-41	400V/50Hz	80	18,0 kg
neu	12	HI-(HF)	2060 W	12,2 A	5112.1600.212	HI 2000/12-135.80.2-37	380-400-420V/50HZ	80	18,0 kg

- screw terminal 2,5 mm²
- number of terminals depending on the model
- terminal mounted on the bottom

Ausführung : 5112.1120.xxx

Ausführung : 5112.1600.xxx

